





## Quick Start Instructions: Bow Trolling Motor Mount Sea Eagle FS1210

### Motor Mount for Bow Mount Trolling Motor (OPTIONAL)

	<p>The FS1210 can accommodate up to a 55 lb thrust bow mount-type trolling motor. A Quick Release Mount will be needed.</p>
	<p>The motor mount hole pattern fits the WaterSnake Quick Release, BassPro composite bracket for Xi Series, MotorGuide Nylon Quick Release Bracket, Minn Kota RTA-17 and MKA-21 quick releases. Other hole patterns can be drilled in the aluminum board, but not all quick release will fit.</p>
	<p><b>Sea Eagle Supplied Hardware</b>        Quick Release Block screws: (screws provided by manufacture are too long for inflatables).        4 - M6 x 40 mm socket head screw</p> <p>Board Mounting Hardware:        4 - 1/4 - 20 x 1 1/4" truss head screws        4 - 5/16 x 1 1/4" flat washers        4 - Low profile knobs</p>
	<p><b>Mount Quick Release</b>        Use M6 x 40 socket head screws to mount the block onto the aluminum motor mount board.</p> <p>Use the hardware provided with the Quick Release Motor Mount to secure the base piece to the motor.</p>

	<p><b>Board to D-Rings</b> Run truss head screws through large washer. Run screws through D-rings.</p>
	<p>Place board with block over screws. Push down on board and secure with low profile knobs.</p> <p>Leave one nut off until the motor is secured with the locking bar.</p>
	<p><b>Mount Motor</b> Place motor onto block. Secure motor with locking bar (pin).</p>
	<p>Secure motor with fourth knob. Connect motor to battery.</p>

Check our website instruction page for more instructions. Please call us if you have any questions.